






Learn more about  
this product




## Your Gateway to Efficient Connectivity

The Q-Cable is a 3 m (9.8 ft) long adapter cable for the Kvaser PCICanx 4xHS and Kvaser PCICan 4xHS boards. A DSUB pin connector connects to the PCICan board, whilst four DSUB pin connectors connect to the CANbus. This variant helps to protect people and equipment from toxic and corrosive gasses by emitting limited smoke and no halogen when exposed to high heat sources.

 **Warranty**  
2-Year warranty. See our general conditions and policies for details.

 **Support**  
Free support for all products by contacting [support@kvaser.com](mailto:support@kvaser.com)

 **EAN**  
73-30130-00340-8

## Major Features

- Adapter cable designed for the Kvaser PCICanx 4xHS and the Kvaser PCICan 4xHS boards.
- One molded 25 pin DSUB connector with thumbscrews that connects to the CAN interface board.
- Four molded 9 pin DSUB connectors with thumbscrews for the CAN bus.

## Support

At Kvaser, we are committed to providing exceptional support for all our accessories, including cables, SD cards, and mounting brackets. Our dedicated support team is here to assist you with any inquiries or issues you may encounter. Whether you need help with installation, troubleshooting, or compatibility questions, we are here to ensure you have a seamless experience with our products.

### Contact Us:

Technical Support: For technical assistance, please reach out to our knowledgeable support team at [support@kvaser.com](mailto:support@kvaser.com)

Documentation and Resources: Access detailed manuals, FAQs, and troubleshooting guides on our website at [www.kvaser.com/support](http://www.kvaser.com/support)

Warranty and Repairs: For warranty information and repair services, please visit [www.kvaser.com/warranty](http://www.kvaser.com/warranty)

## Technical Data

CAN Channels	4
Connector	One 25 pin DSUB Four 9 pin DSUB
Length	3000 mm
Material	ABS plastic
Operating Temperature Range	-30 to +85 °C
Regulatory Compliance	CE
Weight	360 g