

Kvaser D-SUB 9 pin 120 Ohm termination adapter




Learn more about
this product




Your Gateway to Efficient Connectivity

Kvaser D-SUB 9-pin 120 Ohm termination adapter is a CAN adaptor with a 9-pin D-SUB plug connector at one end and a 9-pin D-SUB socket connector at the other. Between CAN High (pin 7) and CAN Low (pin 2) there is a built-in 120 Ohm CAN terminating resistor.

This adapter provides quick and easy termination to any Kvaser high-speed CAN product. The Kvaser CAN termination adapter is used when there is a need to terminate a CAN node without internal termination or when no CAN node is connected to the bus. The Kvaser D-SUB 9-pin 120 Ohm termination adapter has a 9-pin D-SUB plug connector and a 9-pin D-SUB socket connector. A 120 Ohm terminating resistor sits between pins 2 and 7.

 **Warranty**
2-Year warranty. See our general conditions and policies for details.

 **Support**
Free support for all products by contacting support@kvaser.com

 **EAN**
73-30130-00801-4

Kvaser D-SUB 9 pin 120 Ohm termination adapter

Major Features

- 9-pin D-SUB plug connector, 9-pin D-SUB socket connector
- Built-in 120 Ohm CAN terminating resistor
- CE certified

Support

At Kvaser, we are committed to providing exceptional support for all our accessories, including cables, SD cards, and mounting brackets. Our dedicated support team is here to assist you with any inquiries or issues you may encounter. Whether you need help with installation, troubleshooting, or compatibility questions, we are here to ensure you have a seamless experience with our products.

Contact Us:

Technical Support: For technical assistance, please reach out to our knowledgeable support team at support@kvaser.com

Documentation and Resources: Access detailed manuals, FAQs, and troubleshooting guides on our website at www.kvaser.com/support

Warranty and Repairs: For warranty information and repair services, please visit www.kvaser.com/warranty



Technical Data

Connector	1 socket, 1 plug D-SUB 9
Dimensions	31.1 x 12.7 x 17.9 mm
Operating Temperature Range	-40 to +85 °C
Regulatory Compliance	CE
Weight	9 g

Pin assignment

P1	P2
Shell	Shell
9	9
8	8
6	6
5	5
4	4
3	3
7	7
2	2
1	1