

# Kvaser Leaf Light HS v2 M12



## Your Gateway to Efficient Connectivity

The The Leaf Light HS v2 M12 is the marine version of Kvaser's popular Leaf Light v2 interface. This device provides a simple way of connecting a PC with the onboard computer of a marine electronics system by means of its standard USB 2.0 connector and a 5-pin CAN connector.

### Warranty

2-Year warranty. See our general conditions and policies for details.

### Support

Free support for all products by contacting support@kvaser.com

#### EAN

73-30130-00881-6



# Kvaser Leaf Light HS v2 M12

Technical Data

#### **Major Features**

- Standard USB Type A-connector and 5-pin CAN connector.
- Capable of sending up to 8000 messages per second, each time-stamped with 100 microsecond accuracy.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- High-speed CAN connection (compliant with ISO 11898-2), up to 1 Mbit/s.
- Galvanic isolation, enhancing protection from power surges or electrical shocks.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

#### Support

Documentation, Kvaser SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t script language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.

Bit Rate	40 - 1000 kbp/s
CAN Channels	1
Casing Material	PA66
Connector	M12 5-pin
Current Consumption	90 mA
Dimensions	35 x 165 x 17 mm
Error Frame Detection	Yes
Galvanic Isolation	Yes
IP Class	IP40
Operating Systems	Linux, Windows <sup>1</sup>
Operating Temperature	-40 to +70 °C
PC Interface	USB
Regulatory Compliance	CE, FCC
Silent Mode	No
Timestamp Resolution	100 µs
Weight	106 g

<sup>1</sup> Windows 7, 8, 10 (IA-32 and x86-64) Windows 11 (x86-64)

Kvaser AB Aminogatan 25A SE-431 53 Mölndal Sweden Order order@kvaser.com