



Learn more about
this product



Your Gateway to Efficient Connectivity

The Kvaser Leaf Light HS v2 J1939-13 Type II provides a simple way of connecting a PC with the on-board computer of any J1939 compliant vehicle or industrial system. Get diagnostic data by means of its USB 2.0 connector and a 9-pin J1939-13 (Type II) compliant CAN connector, which is colour-coded in green and supports either 250 Kbps or 500 Kbps vehicle networks.



Warranty

2-Year warranty. See our general conditions and policies for details.



Support

Free support for all products by contacting support@kvaser.com



EAN

73-30130-00915-8

Major Features

- Standard USB Type-A connector and a J1939-13 Type II compliant CAN connector.
- Capable of sending up to 8000 messages per second, each time-stamped with 100 microsecond accuracy.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- High-speed CAN connection (compliant with ISO 11898-2), up to 1 Mbit/s.
- Galvanic isolation, enhancing protection from power surges or electrical shocks.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

Support

Documentation, Kvaser SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t script language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.

Technical Data

| | |
|-----------------------------|--------------------------------------|
| Bit Rate | 40-1000 kbp/s |
| Channels | 1 |
| Connector | J1939-13 Type II |
| Current Consumption | Typical 90 mA |
| Dimensions | 35 x 165 x 17 mm incl. strain relief |
| Error Frame Generation | No |
| Error Counters Reading | No |
| Galvanic Isolation | Yes |
| Interfaces | USB, CAN |
| Material | PA66 |
| Messages Per Second Receive | 8000 mps |
| Messages Per Second Sending | 8000 mps |
| Operating Systems | Linux, Windows ¹ |
| Regulatory Compliance | CE, FCC |
| Silent Mode | No |
| Temperature Range | -20 to +70 °C |
| Timestamp Resolution | 100 µs |
| Weight | 155 g |

¹ Windows 7, 8, 10 (IA-32 and x86-64)
Windows 11 (x86-64)