

# Kvaser T-Cannector Expansion L



Learn more about this product





## Your Gateway to Efficient Connectivity

The Kvaser T-Cannector Expansion L, which consists of a base unit and an extension unit, expands the Kvaser T-cannector v2 (00776-5) to a CAN bus hub that in total offers eight D-SUB9 socket connectors.

An adjustable CAN termination load (connecting an optional resistor of 120  $\Omega$  or 60  $\Omega$ ) is provided by the Kvaser T-cannector v2 (Base unit) and thus provides an affordable and safe way of terminating the CAN bus when using Kvaser interfaces on a development board.

When attached and powered via the Kvaser T-cannector v2, the CAN bus hub is also capable of powering bus powered devices, such as Kvaser's Blackbird, Hybrid and Memorator series.

The Kvaser T-Cannector Expansion L product includes:

- Kvaser T-Cannector v2 (Base unit)
- Kvaser T-Cannector Expansion L (Extension unit)

### 🕕 Warranty

2-Year warranty. See our general conditions and policies for details.

### Support

Free support for all products by contacting support@kvaser.com

#### EAN

73-30130-01300-1

# Kvaser T-Cannector Expansion L

b l

**Technical Data** 



#### **Major Features**

- Transforms Kvaser T-Cannector into a longer D-SUB9 socket connector hub.
- Possibility to connect additional expansions.
- Modular, compatible and specifically developed with Kvaser T-cannector v2 (00776-5) for larger CAN bus hubs.
- Adjustable termination via easy-to-use switch (Base unit).
- LED to indicate power on (Base unit).
- Voltage range of 12 V 24 V DC.

CAN Connector	3 sockets, 1 plug D-SUB9 (Base unit) 3 + 1 sockets, 1 plug D-SUB9 (Extension unit)
Can Bit Rate	1 Mbit/s "Classic CAN"
CAN FD Bit Rate	Up to 8 Mbit/s (with correct physical layer implentation)
Dimensions	55 x 90 x 30 mm (Base unit) 51 x 55 x 34 mm (Extension unit)
Galvanic Isolation	No
Operating Temperature Range	-30 to +80 °C
Power Consumption	Typically 20 mW at 12 V DC
Regulatory Compliance	CE
Relative Humidity	0 % to 85 % (non-condensing)
Voltage Range	12-24 V DC, max 2 A
Weight	171 g (Base + Extension)

Included in Kvaser T-Cannector Expansion L (01300-1) is a Base unit and an Extension unit:





Kvaser T-Cannector v2 EAN: 73-30130-00776-5

Kvaser AB

Sweden

Aminogatan 25A SE-431 53 Mölndal **Sales** sales@kvaser.com Support support@kvaser.com Order order@kvaser.com

Kvaser T-Cannector Expansion L

EAN: 73-30130-01300-1



An eight D-SUB9 socket connector hub

kvaser.com